



AGIP OSO S

AGIP OSO S is a line of ashless high quality hydraulic oils specially developed for use in all types of hydraulic systems and equipments.

The oils are formulated from selected paraffinic base stocks treated with antirust, antioxidant and antiwear additives (Classification ISO-L-HM). The oils are available in a wide range of viscosities to suit all practical requirements.

CHARACTERISTICS (TYPICAL FIGURES)

| AGIP OSO S | | 22 | 32 | 46 | 68 | 100 | 150 | 220 |
|----------------------|--------------------|-------|-------|-------|-------|-------|-------|-------|
| Viscosity at 40°C | mm ² /s | 21 | 30 | 45 | 64,3 | 102 | 143 | 221 |
| Viscosity at 100°C | mm ² /s | 4,4 | 5,3 | 6,8 | 8,6 | 11,4 | 14 | 18,7 |
| Viscosity Index | - | 100 | 106 | 105 | 98 | 95 | 95 | 95 |
| Flash Point COC | °C | 205 | 208 | 215 | 220 | 232 | 240 | 240 |
| Pour Point | °C | -30 | -30 | -27 | -24 | -24 | -24 | -21 |
| Mass density at 15°C | kg/l | 0,863 | 0,875 | 0,880 | 0,885 | 0,890 | 0,895 | 0,897 |

PROPERTIES AND PERFORMANCE

- The oils are designed for energy transmission in plants requiring the use of a hydraulic fluid. The oils also provide adequate lubrication by creating a strong lubricant film which withstands high loads between the sliding parts of high-pressure hydraulic systems.
- **AGIP OSO S** oils have very good antiwear properties, as illustrated by typical test results:
 - * vane and ring wear in the Vickers test around 50 mg;
 - * the grade ISO VG 46 passes the 11th stage of the FZG test.
- They have extremely good oxidation resistance and stability even when subjected to unusually high thermal stresses; this property minimizes sludge and deposit formation, thus preventing blocking of ports, valves and controls, while guaranteeing that the oil remains properly fluid. Maintenance costs are therefore reduced and the useful service life of the oil is extended.
- The high Viscosity Index of all grades minimizes changes in viscosity throughout the normal range of operating temperatures, thus ensuring constant flow, low friction loss and good hydraulic efficiency, while protecting against the possibility of cavitation.
- They have a low pour point which allows easy start-up of hydraulic equipment even at low temperatures, without circulation or regulation problems.
- Their outstanding anticorrosion and antirust properties inhibit the oxidation of internal surfaces of hydraulic circuits and therefore prevent operating difficulties and breakdown of the oil caused by metallic oxides that would otherwise form within the machinery.
- Their good demulsibility prevents the formation of a stable emulsion between the oil and any water which enters the system through leakage or condensation. The fluids therefore maintain their lubricating power and anticorrosion performance even under these circumstances.
- Their special formulation guarantee a good filtrability.
- Their antifoam properties and their ready release of entrained air prevent difficulties with pumps and controls which can cause irregularities in performance and other problems arising from the compressibility of air bubbles.

AGIP OSO S



APPLICATIONS

AGIP OSO S fluids are recommended for use in all hydrodynamic power transmission machinery, in hydraulic controls and hydrostatic systems widely used in all fields of technology, such as transport, construction and mining, as well as in chemical and metallurgical machinery, machine tools, marine and aviation equipment etc.. They are suitable for pumps with steel-on-steel and steel-on-bronze contact. AGIP OSO S products are recommended not only for use as hydraulic fluids but also as heavy-duty lubricants for bearings, reduction units, etc., where operating conditions call for special antiwear characteristics.

SPECIFICATIONS

AGIP OSO S products meet the requirements of the following specifications:

- ISO-L-HM
- DIN 51524 t.2 HLP category
- AFNOR NF E 48603 HM
- DENISON HF 2