



## APPLICATIONS

**Eni Kart 2T** is a top synthetic lubricant, its formulation contains castor oil, designed for meet the lubrication requirements of 2-stroke kart engines. It is expressly formulated for the lubrication of engines operating at very high speeds.

## CUSTOMER ADVANTAGES

- The special formulation of **Eni Kart 2T** ensures perfect lubrication of the surfaces, the product has exceptional anti-seize properties.
- The particular choice of components in the formulation allows obtaining a high detergency of the mechanical components, with an excellent protection against wear phenomena and a thermo-oxidative stability at high temperatures.
- The product allows a perfect control of the deposits that may build up in the exhaust port and combustion chamber.
- **Eni Kart 2T** is suitable for use in a mixture with gasoline, in air-cooled or liquid-cooled engines.
- It is recommended to prepare the mixture manually, respecting the percentages and recommendations provided by the manufacturer.
- During the preparation of the mixture it is advisable to shake the product for a few minutes before mixing it with gasoline.

## CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m <sup>3</sup>	908
Viscosity at 100°C	ASTM D 445	mm <sup>2</sup> /s	10.7
Viscosity at 40°C	ASTM D 445	mm <sup>2</sup> /s	69
Viscosity Index	ASTM D 2270	-	144
Flash point (COC)	ASTM D 92	°C	220

