



## APPLICATIONS

**Eni Geum LFG 40** is a lubricant for modern stationary engines, spark-ignition type, burning landfill gas, biogas or other fermentation gases (digestors). **Eni Geum LFG 40** is formulated with high Viscosity Index basestocks and selected additives that deliver detergent-dispersant, antiwear and antifoam properties. The product retains a particularly high resistance to oxidation processes and low content of phosphorus.

## CUSTOMER ADVANTAGES

- Prevention of deposits and lacquers formation on pistons and valves for an outstanding engine cleanliness
- Protection of lubricated components from mechanical wear
- Particularly extended oil drain intervals

## SPECIFICATIONS & APPROVALS

- GE Jenbacher engines type 2/3/4/6 on gas class B and C
- MAN M 3271-4

## CHARACTERISTICS

Properties	Method	Unit	Typical
Appearance	APM 27	-	clear
Density at 15°C	ASTM D 4052	kg/m <sup>3</sup>	873
Viscosity at 100°C	ASTM D 445	mm <sup>2</sup> /s	13.4
Viscosity index	ASTM D 2270	-	110
Flash point (COC)	ASTM D 92	°C	231
Pour point	ASTM D 97	°C	-30
B.N.	ASTM D 2896	mgKOH/g	4.5

