

Eni i-Sea outboard 4T 10W-40



APPLICATIONS

Eni i-Sea outboard 4T 10W-40 is a universal lubricant for 4-stroke outboard motors.

CUSTOMER ADVANTAGES

- It is formulated with high technology components that allow the engine to express its maximum performance, while protecting it from mechanical wear and saline corrosion, even in case of prolonged inactivity.
- It keeps the engine clean avoiding the formation of carbon deposits to ensure maximum reliability of operation and long life to all lubricated parts.
- It effectively contrasts the adverse effects of lubricant dilution in the fuel, which are particularly significant in the case of prolonged operation of the engine at minimum speeds.
- It allows to minimize the formation of sludge in the engine avoiding the risk of occlusion of the filters.
- It has been successfully subjected to the most stringent performance tests (the product achieves a NMMA FC-W® performance level).

SPECIFICATIONS - APPROVALS

- API SL
- NMMA FC-W



Eni i-Sea outboard 4T 10W-40



CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m ³	860
Viscosity at 100°C	ASTM D 445	mm ² /s	14.4
Viscosity at 40°C	ASTM D 446	mm ² /s	95
Viscosity Index	ASTM D 2270	-	175
Viscosity at -25°C	ASTM D 5293	mPa·s	3450
Flash point (COC)	ASTM D 92	°C	220
Pour point	ASTM D 97	°C	-27

