



APPLICATIONS

Eni Aquamet CL 33 is a cleaning product for tanks and the circuits of the machine tool where water-miscible lubricants are used.

Recommended for single and centralized plants.

CUSTOMER ADVANTAGES

- It removes sludge and residues from circuits and tanks of the machine tool
- The product can be added directly to the tank of the exhausted emulsion during the last shift
- The effective cleaning of the system by **Eni Aquamet CL 33** increases the life of the new emulsion

CHARACTERISTICS

Properties	Method	Unit	Typical
Appearance	-	-	limpid
Colour	-	-	light yellow
Density at 15°C	ASTM D 1298	kg/m ³	1060
pH emuls. 5%	ASTM D 1287	-	11.0

WARNINGS

- For an effective detergent action, add **Eni Aquamet CL 33** directly in the exhausted emulsion during the last working shift and let it circulate for 8-12 hours before discharge. At the end of this period, drain the tank and rinse the system with clean water. During this operation it is possible a slight foam formation.





- The usual concentration of use is 2%. In case of very dirty systems, the concentration can be increased to 3%.
- More detailed information will be provided by the Eni Technical Assistance Service.
- To prevent the product deterioration, due to the thermal shocks, store the product in closed warehouses at temperature between +5 and +30°C.
- Handle the product according to the good hygiene and safety standards.
- More detailed information will be provided in the Safety Data Sheet.

