



APPLICATIONS

Eni i-Sint Top Rally 10W-50 is an innovative lubricant with fully synthetic formulation containing PAO developed to meet the lubrication requirements of engines that operate in extreme conditions such as competition engines with high specific powers, driving conditions (eg rallying), off-road engines operating at high temperatures (desert).

CUSTOMER ADVANTAGES

- The exclusive formulation of the **Eni i-Sint Top Rally 10W-50** has characteristics that offer maximum performance even in the presence of particularly high stresses.
- The high quality base stocks and in particular the presence of PAO (Poly-alpha-olefin) ensure the product an extraordinary thermo-oxidative stability.
- The viscosimetric characteristics of the product guarantee excellent lubrication of the mechanical components of the engine in any operating condition and temperature, even after prolonged periods of use.
- **Eni i-Sint Top Rally 10W-50** is capable of ensuring a good engine detergency, in particular it has characteristics that allow efficient control of the formation of deposits areas submitted to high temperature.

SPECIFICATIONS - APPROVALS

- API SN





CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/dm ³	0.854
Viscosity at 100°C	ASTM D 445	mm ² /s	17.94
Viscosity at 40°C	ASTM D 445	mm ² /s	118.4
Viscosity Index	ASTM D 2270	-	169
Viscosity at -25°C	ASTM D 5293	mm ² /s	4834
Pour point	ASTM D 97	°C	-36
Flash point (COC)	ASTM D 92	°C	242

