



## APPLICATIONS

**Eni i-Sint Extra Tec 5W-40** is a high performance fully synthetic lubricant designed to meet the requirements of advanced-technology cars and light commercial vehicles equipped with gasoline or Diesel engines.

## CUSTOMER ADVANTAGES

- **Eni i-Sint Extra Tec 5W-40** is distinguished by an ideal combination of viscosity, lubrication and detergency to minimize the formation of deposits and to ensure effective protection of mechanical components.
- **Eni i-Sint Extra Tec 5W-40** maintains an ideal viscosity in a wide range of engine operating conditions, reduces friction losses, resulting in fuel saving and reduced CO2 emissions.
- The product is characterized by a low volatility that contributes to limiting engine oil consumption.
- The thermo-oxidative properties give the product resistance to deterioration in operation, in conditions of prolonged exposure to high temperatures in the presence of air and other agents.
- Thanks to its formulation and performances, **Eni i-Sint Extra Tec 5W-40** meets the severe requirements of many important European OEMs.

## SPECIFICATIONS - APPROVALS

- API SN/CF
- ACEA A3/B4
- MB 229.3
- MB 226.5
- PORSCHE A40
- VW 502 00 + 505 00
- Renault RN 0700 0710





## CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/dm <sup>3</sup>	
Viscosity at 100°C	ASTM D 445	mm <sup>2</sup> /s	14.07
Viscosity at 40°C	ASTM D 445	mm <sup>2</sup> /s	84.25
Viscosity Index	ASTM D 2270	-	173
Viscosity at -30°C	ASTM D 5293	cP	6269
Pour point	ASTM D 97	°C	-39
Flash point (COC)	ASTM D 92	°C	232

