



## APPLICATIONS

**Eni i-Sint pro light 5W-30** is an innovative synthetic technology lubricant with "Mid SAPS" (MS) characteristics, specifically formulated for gasoline or diesel engines of the latest models of passenger cars and light vans.

## CUSTOMER ADVANTAGES

- Its 'mid SAPS' (MS) characteristics ensure efficiency and durability of after-treatment devices.
- **Eni i-Sint pro light 5W-30** allows easier engine startup and give high fuel economy benefits, with consequent reduction of CO2 emissions.
- Its high quality formulation has been developed to meet the severe requirements of many European OEMs. In particular it strongly resists to high temperatures oxidation in presence of air and other agents, allowing longer drain intervals.

## SPECIFICATIONS - APPROVALS

- API SN/CF
- ACEA C3
- MB 229.51
- BMW LL-04
- GM DEXOS 2





## CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/dm <sup>3</sup>	0.851
Viscosity at 100°C	ASTM D 445	mm <sup>2</sup> /s	11.57
Viscosity at 40°C	ASTM D 445	mm <sup>2</sup> /s	67.78
Viscosity Index	ASTM D 2270	-	166
Viscosity at -30°C	ASTM D 5293	cP	6160
Flash point (COC)	ASTM D 92	°C	240
Pour point	ASTM D 6749/9	°C	-39

