



APPLICATIONS

Eni i-Sint Super 5W-40 is a high performance fully synthetic lubricant designed to meet the requirements of advanced-technology cars equipped with gasoline engines.

CUSTOMER ADVANTAGES

- **Eni i-Sint Super 5W-40** is characterized by a low volatility that contributes to limiting engine oil consumption.
- **Eni i-Sint Super 5W-40** maintains an ideal viscosity in a wide range of engine operating conditions, reduces friction losses, resulting in fuel saving and reduced CO2 emissions.
- The components included in the formulation have the ability to adhere to metal surfaces, even for extended engine stop periods, facilitating starting and limiting the wear phenomena.
- Thanks to its formulation, **Eni i-Sint Super 5W-40** helps to minimize the formation of deposits and to ensure effective protection of mechanical components.
- The thermo-oxidative properties give the product resistance to deterioration in operation, in conditions of prolonged exposure to high temperatures in the presence of air and other agents.

SPECIFICATIONS - APPROVALS

- API SN





CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/l	0.851
Viscosity at 100°C	ASTM D 445	cSt	13.89
Viscosity at 40°C	ASTM D 445	cSt	83.66
Viscosity Index	ASTM D 2270	-	171
Viscosity at -30°C	ASTM D 5293	mPa·s	5718
Flash point (COC)	ASTM D 92	°C	236
Pour point	ASTM D 6749/9	°C	-36

