



## APPLICATIONS

**Eni i-Sint Rally 10W-50** is a lubricant with synthetic technology formulation suitable for engines that operate in extreme conditions such as competition engines with high specific powers, driving conditions (eg rallying), off-road engines operating at high temperatures (desert).

## CUSTOMER ADVANTAGES

- The viscosimetric characteristics of the product guarantee excellent lubrication of the mechanical components of the engine in any operating condition and temperature, even after prolonged periods of use.
- The particular selection of the components used in the formulation considerably reduces the effects linked to the volatility and at the same time allows a high thermal stability.
- **Eni i-Sint Rally 10W-50** is capable of ensuring a good engine detergency, in particular it has characteristics that allow efficient control of the formation of deposits areas submitted to high temperature.

## SPECIFICATIONS - APPROVALS

- API SN





## CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/l	0.867
Viscosity at 100°C	ASTM D 445	mm <sup>2</sup> /s	19.31
Viscosity at 40°C	ASTM D 445	mm <sup>2</sup> /s	135.2
Viscosity Index	ASTM D 2270	-	163
Viscosity at -25°C	ASTM D 5293	cP	6273
Flash point (COC)	ASTM D 92	°C	234
Pour point	ASTM 6749/9	°C	-36

