



APPLICATIONS

Eni Rotra ATF MB BX is a very high graded automatic transmission fluid formulated with a number of special selected base oils and additives.

CUSTOMER ADVANTAGES

- Very good stability against oxidation.
- Very low pour point.
- Positive activity against wear, corrosion and foam.
- Constant friction stability over lifetime ensuring perfect clutch operation.
- Extremely resistant against shudder vibration.
- It is typically coloured red.

SPECIFICATIONS - APPROVALS

- MB 236.14
- ALLISON C-4 Level
- DEXRON II
- DEXRON IIIH
- Ford WSS-M2C922-A1
- Isuzu ATF II/III
- Jaguar JLM 20238/20292/21044
- JASO M315 Type 1A
- Mazda M-III
- Mitsubishi SP-II/SP-III/ATF J-2
- Subaru ATF HP
- Suzuki ATF 3314/3317
- VAG G-052-025
- VAG G-052-055
- VAG G-052-162





- VAG G-052-990
- VAG G-055-025
- Volvo 1161540
- ZF TE-ML 11A/11B

CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m ³	855
Viscosity at 40°C	ASTM D 445	mm ² /s	29.6
Viscosity at 100°C	ASTM D 445	mm ² /s	6.5
Viscosity Index	ASTM D 2270	-	185
Flash point COC	ASTM D 92	°C	> 200
Pour point	ASTM D 97	°C	-60