



## APPLICATIONS

**Eni Antifreeze Spezial BX** is an ethylene glycol based fluid that provides maintenance-free protection against freezing and boiling but also against corrosion.

## CUSTOMER ADVANTAGES

- **Eni Antifreeze Spezial BX** is suitable to use in engines manufactured from cast iron, aluminium or combinations of the two metals, and in cooling systems made of aluminium or copper alloys.
- It provides long-life protection against all forms of corrosion by the use of optimized and patented organic corrosion inhibitors.

## SPECIFICATIONS - APPROVALS

- MB 325.3
- ASTM D 3306
- FORD WSS-M97B44-D
- OPEL GM 6277M
- MAN 324 Tipo SNF
- VW TL 774 D/F (G12/G12+)





## CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 20°C		kg/l	1.11
pH	ASTM D 1287	-	8.6
Boiling point	ASTM D 1120	°C	180
Alkaline reserve	ASTM D 1121	-	6.2

## WARNINGS

- To profit from the performance of this product, a mixture with other coolants is not advised.
- Please respect strictly the product specification requirements reported by the vehicle manufacturer or machinery supplier.

## HANDLING INFORMATION

- The product has to be diluted with water before use. Best working conditions are obtained by diluting with good quality water in a 33 - 60% range by volume.
- Distilled or demineralised waters suggested.
- Freezing and boiling point of the coolant depend on the concentration of the product in water:

Volume%	Freezing Point (° C)	Boiling Point (° C)
33	-20	104
50	-40	108

