



APPLICATIONS

Eni Antifreeze Plus BX is an ethylene glycol based fluid exempt from nitrites, amines and phosphates, recommended for use in cooling systems of all types liquid cooled automotive and industrial internal combustion engines.

CUSTOMER ADVANTAGES

- **Eni Antifreeze Plus BX** provides efficient and long lasting corrosion protection.
- It has excellent seal compatibility without no adverse effects on rubber hoses and gasket materials.

SPECIFICATIONS - APPROVALS

- ASTM D 3306
- BMW
- OPEL
- MASERATI
- NATO S-759
- VOLVO
- VW TL 774 C (G11)
- IVECO
- MAN 324 Typ NF level
- BS 6580





CHARACTERISTICS

| Properties | Method | Unit | Typical |
|------------------|-------------|--------------------|---------|
| Density at 20°C | | kg/dm ³ | 1.12 |
| pH | ASTM D 1287 | - | 7.2 |
| Boiling point | ASTM D 1120 | °C | 174 |
| Alkaline reserve | ASTM D 1121 | - | 16 |

WARNINGS

- To profit from the performance of this product, a mixture with other coolants is not advised.
- Please respect strictly the product specification requirements reported by the vehicle manufacturer or machinery supplier.

HANDLING INFORMATION

- The product has to be diluted with water before use. Best working conditions are obtained by diluting with good quality water in a 33 - 60% range by volume.
- Distilled or demineralised waters suggested.
- Freezing and boiling point of the coolant depend on the concentration of the product in water:

| Volume% | Freezing Point (° C) | Boiling Point (° C) |
|---------|----------------------|---------------------|
| 33 | -20 | 104 |
| 50 | -40 | 108 |

